MATERIAL SAFETY DATA SHEET
MAY BE USED TO COMPLY WITH
OSHA'S HAZARD COMMUNICATION STANDARD
CFR 1910.1200. STANDARD MUST BE
CONSULTED FOR SPECIFIC REQUIREMENTS

Services to the Sciences Since 1924

CARGILLE LABORATORIES, INC.
55 Commerce Road • Cedar Grove, New Jersey • 07009-1289 USA
Phone: 973-239-6633 Fax: 973-239-6096 Email: CargilleLabs@aol.com URL: http://www.cargille.com

CATALOG #16485

IDENTITY (AS USED ON LABEL AND MANUF. LITERATURE)	NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, OR NO INFORMATION IS AVAILABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.
CARGILLE IMMERSION OIL **TYPE NVH CODE 658**	

SECTION 1

MANUFACTURER'S NAME CARGILLE LABORATORIES, INC.	EMERGENCY TELEPHONE NUMBER WEEKDAY 973 - 239 - 6633 24 HR CHEMTREC 800 - 424 - 9300	
ADDRESS (NUMBER, STREET, CITY, STATE, AND ZIP CODE)	TELEPHONE NUMBER FOR INFORMATION 973 – 239 - 6633	
55 COMMERCE ROAD	DATE PREPARED MAY 23, 2011	SUPERCEDES PRIOR DATED MSDS FOR THIS MATERIAL
CEDAR GROVE, NJ 07009	SIGNATURE OF PREPARER (OPTIONAL)	

THE INFORMATION SUPPLIED IS BASED ON DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION PRESENTED AND CARGILLE LABORATORIES ASSUMES NO RESPONSIBILITY FOR THE RESULTS OF THE USE OF THIS PRODUCT. THIS INFORMATION IS FURNISHED UPON THE CONDITION THAT THE PERSON RESPONSIBLE FOR ITS USE SHALL MAKE HIS OR HER OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS OR HER PARTICULAR PURPOSE.

CONDITIONS OF **I**NTENDED AND NORMAL **U**SE: (ABBR. C.I.U.) AS A MICROSCOPE IMMERSION OIL AT NORMAL ROOM PRESSURE (760 mm HG), TEMPERATURE 45 °F TO 104 °F IN A NON MISTED / NON AIRBORN STATE IN A ROOM HAVING NORMAL AIR CHANGES, (2) / HR., IN A TRAINED AND SUPERVISED LABORATORY / INDUSTRIAL SETTING USING STANDARD GL / GM PROCEDURES. SEE SECTIONS 7 AND 8

SECTION 2 - HAZARDOUS INGREDIENTS

SPECIFIC CHEMICAL IDENTITY INFORMATION

HAZARDOUS COMPONENTS	(COMMON NAME (S))	OSHA PEL CEILING	ACGIH TLV T.W.A.	OTHER LIMITS RECOMMENDED	% (OPTIONAL)
TRADE SECRET	HYDROGENATED TERPHENYL	N.E.	5 mg / CUBIC METER *		
TRADE SECRET	TERPHENYL	5 mg / CUBIC METER *	5 mg / CUBIC METER *		
TRADE SECRET	POLYBUTENES	5 mg / CUBIC METER *	5 mg / CUBIC METER *		

*PEL CEILINGS & TLV T.W.A.s IF ANY SHOULD NOT OCCUR IF C.I.U. AND SECTIONS 7 & 8 FOLLOWED.

NOTE: PRODUCT NORMALLY SOLD IN ¼ OZ. TO 1 GALLON QUANTITIES. USED IN SINGLE DROP TO A FEW CUBIC CENTIMETERS PER APPLICATION. SEE REQUISITIONER FOR SPECIFIC QUANTITIES INVOLVED.

SECTION 3 - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT AT 760 mm HG 340 °C	644 °F	SPECIFIC GRAVITY (H_2O = 1) TEMP. 23 °C / 73 °F	.9
VAPOR PRESSURE IN mm HG (TEMP.) 73 °F	< 0.1	MELTING POINT	< 32 °F
VAPOR DENSITY (AIR = 1) AT (mm HG & TEMP.) 760 73 °F	ca 1	EVAPORATION RATE AT 760 mm HG & 23 °C / 73 °F (MINERAL OIL = 1)	ca 1
SOLUBILITY IN WATER AT (mm HG & TEMP.) 760 73 °F	NIL	APPEARANCE AND ODOR LIGHT YELLOW, SLIGHT CHARACTERISTIC ODOR	

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (CUP METHOD USED) > 325 °F (163 °C) C.O.C.	FLAMMABLE LIMITS	LEL N.D.F.	UEL N.D.F.

EXTINGUISHING MEDIA: CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR ANY CLASS B AGENT

SPECIAL FIRE FIGHTING PROCEDURES: NONE

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

ABBREVIATIONS: N.A. = NOT APPLICABLE; N.D.F. = NO DATA FOUND; TR.S. = TRADE SECRET; N.E. = NOT ESTABLISHED; C.I.U. = CONDITIONS OF INTENDED USE; < = LESS THAN; > = GREATER THAN.

SECTION 5 - REACTIVITY DATA

STABILITY	UNSTABLE		
	STABLE	YES	

INCOMPATIBILITY (MATERIALS AND / OR CONDITIONS TO AVOID)

STRONG OXIDIZERS, HEAT ABOVE 150 °F

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	N.A.

SECTION 6 - HEALTH HAZARD DATA

ROUTE (S) OF ENTRY:	INHALATION?	SKIN?	MUCOUS MEMBRANES / EYES?	INGESTION?
(NOT LIKELY AT C.I.U.)	YES	SLIGHT	SLIGHT	POSSIBLE

HEALTH HAZARDS (ACUTE AND CHRONIC).

NONE KNOWN AT C.I.U.

CARCINOGENICITY LISTED:	NTP?	IARC MONOGRAPHS?	OSHA CARCINOGEN?
	NO	NO	NO

SIGNS AND SYMPTOMS OF EXPOSURE

OILY FEEL, IF LIQUID IS MISTED OR ABOVE 150 °F (NOT A C.I.U.) HEADACHES AND NAUSEA POSSIBLE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

N.D.F.

EMERGENCY AND FIRST AID PROCEDURES: INCLUDE POSSIBLE MATERIAL THAT MAY HAVE BEEN MIXED WITH LIQUID DURING USE.

INHALATION – (NOT LIKELY AT C.I.U.) IF CONCERN ARISES, REMOVE TO FRESH AIR.

SKIN & CLOTHES – PROMPT SOAP AND WATER WASH.

EYES – FLUSH WITH WATER, SLIGHT TEMPORARY IRRITATION POSSIBLE (CONSULT PHYSICIAN).

INGESTION – LOW ORDER OF TOXICITY , FIRST AID NORMALLY NOT NEEDED (CONSULT PHYSICIAN).

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE – FOLLOW C.I.U. SEE SECTION 1

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ABSORB, PLACE IN PLASTIC (POLYETHYLENE OR POLYPROPYLENE) CONTAINER, CAP OR TWIST TIE CLOSURE (SEE SECTION 8).

WASTE DISPOSAL METHOD:

ALL CHEMICAL DISPOSALS MUST BE IN ACCORDANCE WITH CURRENT LOCAL, STATE, AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BETWEEN 65 °F AND 90 °F (18 °C AND 32 °C)

OTHER PRECAUTIONS

AVOID CONTINUAL DIRECT SUNLIGHT, VAPORIZING OR ATOMIZING.

SECTION 8 - CONTROL MEASURES; WHEN USED AS INTENDED (SEE SECTION 1)

RESPIRATORY PROTECTION (SPECIFY TYPE)

SEE "VENTILATION"

VENTILATION	LOCAL EXHAUST *	SPECIAL N.A.
	MECHANICAL (GENERAL) *	OTHER N.A.

PROTECTIVE GLOVES * SURGICAL TYPE , IF WORN	EYE PROTECTION *

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

*

* = NOT MANDATORY EXCEPT AS GOOD LABORATORY INDUSTRIAL PRACTICES.
ALWAYS USE GOOD HYGIENIC WORK / PRACTICES AS TO HOUSEKEEPING, PERSONAL HYGIENE, USE OF CHEMICAL LAB APRON AND SPLASH GOGGLES, AVOIDANCE OF VAPORS, PROLONGED AND REPEATED SKIN CONTACT.

SPECIAL PRECAUTIONS

N.A.